



Diesel Driven Generator Model WH5500DGS



A simple to operate generator in an attenuated enclosure. Provided with wheels and handles at either end for manouvreability.

These packaged generator units feature single cylinder, type WD406 10HP vertical, 4 stroke, air cooled, direct injection, diesel engines. Rated rotation speed 3000rpm. Electric key start is standard on these models.

The generator is a brushless, revolving field, self exciting type offering a maximum of 5.5kVA in various voltage configurations.

Model 1-

~~400/3/50 + 230/1/50 + 12Vdc (8Amp).~~
~~(1 x 400V and 2 x 230V sockets)~~

Model 2.

230/1/50 + 110/1/50 + 12Vdc (8Amp).
 (1 x 110V and 2 x 230V sockets)



Control Panel Features:

- DC Circuit Protector • DC Terminals
- Low Oil Warning Light • Sockets
- Voltage Selector Switch • Volt Meter
- Ground Earth Terminal • Key Start
- On/Off Switch • Circuit Breaker

ENGINE TECHNICAL DATA

MODEL	Engine Type	Engine cc	Max Output HP/rpm	Fuel Volume	Run Time Full Tank	Start Method
WH5500DGS	WD406	406	10/3600	12.5 L	12 Hrs.	Electric

GENERATOR TECHNICAL DATA

MODEL	Max kVA Output	Voltages 1-Ph	Voltages 3-Ph/1-Ph	DC Output Volt/Amp	Noise Level dB(A) - 7m Full Load	Package Dim. mm L x W x H	Net /Gross Weight Kg
WH5500DGS	5.5	110/230	400/230	12V/8A	76	950x565x770	161/171

© Descriptions, technical data and features contained in this leaflet are not binding. We reserve the right to make any necessary modifications without prior notice.

