



Petrol Driven 2.5kW and 6.0kW Generators



WH3500



WK3500



WK7500E

These packaged generator units feature single cylinder, 4 stroke, air cooled, OHV, petrol engines running on standard automotive unleaded fuel.

Units are mounted on anti-vibration rubber feet and housed within a protective tube steel frame. They are fitted with wheels and guide handles for simple manoeuvrability.

Using standard SAE10W30 lube oil, a low oil level safety cut-out device is fitted on all models.

All three models offer a combination of 110/1/50 and 230/1/50 output sockets.

Type WH models have a metal fuel tank, whilst Type WK have larger plastic tanks. All tanks have fuel indicators.

Other petrol and diesel driven generator sets available. Please contact the Sales Office.

MOTOR TECHNICAL DATA

MODEL	Motor Type	Motor cc	Max Output HP/rpm	Fuel Volume	Start Method
WH3500	WG200	200	6.7/3600	12 L	Recoil
WK3500	WG200	200	6.7/3600	20 L	Recoil
WK7500E	WG405	407	14.0/3600	28 L	Elect/Recoil

GENERATOR TECHNICAL DATA

MODEL	kW Rating	Max kW Output	Voltages 1-Ph/50Hz	Noise Level dB(A) - 7m Zero Load/Full Load	Package Dim. mm L x W x H	Package Weight Kg
WH3500	2.5	2.8	110/230	70 - 72	560x450x500	43
WK3500	2.5	2.8	110/230	70 - 72	560x450x500	43
WK7500E	6.0	6.5	110/230	70 - 74	630x535x635	82

© Descriptions, technical data and features contained in this leaflet are not binding. We reserve the right to make any necessary modifications without prior notice.

